


भारतीय सांख्यिकी संस्थान
दिल्ली केंद्र



ग्राम स्टैटिस्टिक्स, नई दिल्ली

फ़ोन : .41493984

फैक्स : 41493981

ईमेल : kalam@isid.ac.in

7, एस जे एस, सनसनवाल मार्ग,
क़तूब होटल के पास
कटवरिया सराय
नई दिल्ली

निविदा आमंत्रित सूचना

निविदा नं. D /ISI /CIVIL WORK /2016 -2017 / 216

मोहरबंद लिफाफे में भरे हुए विवरण(quotation) आमंत्रित किए जाते हैं . विवरण(quotation) तारीख 10/07/2016 या उससे पहले इस कार्यालय को 3.00 बजे तक मिलने चाहिये . विवरण(quotation) उसी दिन आपके समक्ष या आपके अनुपस्थिति में 3.30 बजे खोले जायेंगे .

Name of work - Painting and aluminium door work in Library Building in ISI Campus Delhi Centre, New Delhi-110016.

| Sr No. | Description of item of work | Unit | Qty | Rate | Amount |
|--------|--|-------|---------|------|--------|
| 1 | Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete | sqm | 934.89 | | |
| 2 | Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade : | sqm | 934.89 | | |
| | Old work (one or more coats) | | | | |
| 3 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | sqm | 34.596 | | |
| 4 | Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade : | | | | |
| | Old work (one or more coats) | sqm | 34.596 | | |
| 5 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the lastered wall surface to prepare the surface even and smooth complete. | | | | |
| | same as item 1-40% paid only | sqm | 373.95 | | |
| | same as item 4 | sqm | 13.838 | | |
| 6 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : | sqm | 131.308 | | |
| | One or more coats on old work | | | | |
| 7 | Repainting G.I. pipes and fittings with synthetic enamel white paint with one coat of approved quality : | meter | 30 | | |
| | 50 mm diameter pipe | | | | |
| 8 | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : | | | | |

| Sr No | Description of item of work | Unit | Qty | Rate | Amount |
|-------|---|-------|-------|-------|--------|
| | For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) | | | | |
| | Powder coated aluminium (minimum thickness of powder coating 50 micron) | kg | 48.09 | | |
| 9 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): | | | | |
| | With float glass panes of 8 mm thickness | sqm | 6.16 | | |
| 10 | Providing and fixing double action hydraulic floor spring of approved brand and manufacture conforming to IS : 6315, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 125 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer box with slide plate etc. complete as per the direction of Engineer-in-charge. | | | | |
| | With stainless steel cover plate minimum 1.25 mm thickness | each | 1 | | |
| 11 | Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. complete as per direction of Engineerin-charge | | | | |
| | Powder coated minimum thickness 50 micron aluminium | each | 2 | | |
| 12 | Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete. | each | 1 | | |
| 13 | Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete. | | | | |
| | Twin rubber stopper | each | 2 | | |
| 14 | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : | | | | |
| | 250x10 mm | each | 2 | | |
| 15 | Providing and fixing ISI marked aluminium butt hinges anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete: | | | | |
| | 100x75x4 mm | each | 3 | | |
| 16 | Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete : | | | | |
| | 300x16 mm | each | 1 | | |
| 17 | Filling the gap in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete. | | | | |
| | Upto 5mm depth and 5 mm width | meter | 7.8 | | |
| | Total (inclusive taxes) | | | Total | |