

ग्राम स्टैटिस्टिक्स, नई दिल्ली

फोन : 41493984

फैक्स : 41493981

ईमेल : kalam@isid.ac.in



7, एस जे एस, सनसनवाल मार्ग,
कुतुब होटल के पास
कटवरिया सराय
नई दिल्ली

निविदा आमंत्रित सूचना

निविदा नं. D/ISI/CIVIL WORK/2016-2017/ 258

मोहरबंद लिफाफे में भरे हुए विवरण(quotation) आमंत्रित किए जाते हैं . विवरण(quotation) तारीख 23/01/2017 या उससे पहले इस कार्यालय को 3.00 बजे तक मिलने चाहिये . विवरण(quotation) उसी दिन आपके समक्ष या आपके अनुपस्थिति में 3.30 बजे खोले जायेंगे .

Providing and Fixing of looking mirror glass and seepage work (civil work) side of reception room in Faculty Building second floor

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
1	providing and fixing of ply 6 mm thick	sqm	12		
2	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately)				
	Second class teak wood	cum	0.12		
3	Providing and fixing wooden moulded beading to door and window frames with iron screws, plugs and priming coat on unexposed surface etc. complete :				
	2nd class teak wood				
	50x12 mm				
4	Polishing on wood work with ready mixed wax polish of approved brand and manufacture :	meter	36		
	Applying priming coat :				
5	With ready mixed pink or Grey primer of approved brand and manufacture on resinous wood and plywood	sqm	3.3		
6	Providing and Fixing of 5 mm looking mirror glass	sqm	12		
	civil work				
7	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
	For thickness of tiles above 25 mm and up to 40 mm	sqm	19.25		
8	Dismantling of flushing cistern of all types (C.I./PVC/Vitreous China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead.	each	8		
9	Providing and fixing water closet squatting pan (Indian type W.C. pan) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:				
	White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests				
	indian wc	each	2		

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
10	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required. W.C. pan with ISI marked white solid plastic seat and lid european wc				
11	Dismantling old C.I. pipes including excavation and refilling trenches after taking out the pipes, breaking lead caulked joints, melting of lead and making into blocks, including stacking of pipes at site lead up to 50 metre: 100 mm diameter C.I. pipe	each	2		
12	Providing and laying S&S C.I. Standard specials such as tees, bends, collars tapers and caps etc, suitable for flanged jointing as per IS : 1538 :	meter	12		
a	p-trap-4"				
b	bend-90deg-4"	each	2		
c	p-trap-3"	each	3		
d	door bend-3"	each	2		
e	door tee-3"	each	3		
f	plain bend-3"	each	3		
g	door bend-4"	each	2		
h	door tee-4"	each	3		
i	plain tee-4"	each	1		
j	socket-3"	each	1		
k	socket-4"	each	3		
13	Providing and laying S&S centrifugally cast (spun) iron pipes (Class LA) conforming to IS - 1536 : 100 mm dia pipe	each	3		
14	providing and fixing cp jali drain floor Health Faucet	meter each	12 4		
15	Providing and fixing of Health Faucet Abs With Double Lock 1.2 Meter Stainless Steel Flexible Hose And Wall Hook	each	2		
16	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 a) 15 mm nominal bore 15mm nominal bore with wall flange				
	TILE FLOORING	each	2		
17	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	sqm	19.25		
18	Removinnng and refixing of door shutter with fitting REPAIRS TO BUILDING	each	2		

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
19	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per directions of Engineer-In-Charge.				
	With cement mortar 1:4 (1 cement : 4 fine sand)				
	FINISHING	sqm	19.25		
20	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm	126.668		
21	Distemping with dry distemper of approved brand and manufacture (one or more coats) and of required shade on old work to give an even shade.	sqm	126.668		
22	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying : a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours. The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.	sqm	19.25		
23	MALABA REMOVING				
24	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete	l/s	1 job		
	inclusive taxes	sqm	126.668		
				Total	

अभियंता सिविल 'अ'
सूचना

Beharand
16/1/17

मार्क अलम
ओएसडी
16/1/2017

1. प्रस्ताव देने के पहले विवरणकर्ता(quotationer) का जगह को देखना अनिवार्य है .
2. कार्य विवरण(specification) सहित व सिविल अभियंता के शमकश होना चाहिये .
3. कार्य आदेश मिलने के बाद 15 दिन के भीतर कार्य समाप्त होना चाहिए.
4. विवरणकर्ता(quotationer) विवरण फार्म(quotation) के साथ "डी वट" "पन नम्बर " "टिन नम्बर " लगाना अनिवार्य है .
5. The quantity will be increased or decreased as per the actual site condition.
6. विवरण फार्म(quotation) सिग्नेचर किये बगैर और स्टाम्प लगाये बगैर मिला तो सीधे सीधे निरस्त किया जाएगा .
7. कोटेशन में दिए गए आपके कुल राशि पर टैक्सेज एप्लीकेबल रहेंगे.
8. माल दुलाई का अतिरिक्त किराया भाड़ा या कुरियर भाड़ा नहीं दिया जायेगा.
9. सिक्योरिटी डिपाजिट 4% सुरक्षित जमा राशि आपके कुल राशि पर 6 महीने के लिए वैध रहेगी.
10. एडवांस राशि काम के पहले या बाद में एप्लीकेबल नहीं रहेंगे .
11. काम करते समय किसी भी प्रकार का हादसे के लिए ISI Delhi Centre जिमेदार नहीं रहेगी.
12. The ISI Delhi Centre reserve the right the whole tender process may be treated as a cancelled/terminated at any stage without assisgning any reason.

प्रति :-

1. सूचना पलट

1. वेब स्थल आई एस आई दिल्ली केन्द्र