

भारतीय सांख्यिकी संस्थान
दिल्ली केंद्र

ग्राम स्टाटिस्टिका , नई दिल्ली
फ़ोन : 41493984
फैक्स : 41493981
ईमेल : kalam@isid.ac.in



7, एस जे एस, सनसनवाल मार्ग,
कुतुब होटल के पास
कटवरिया सराय नई दिल्ली

निविदा आमंत्रित सूचना

Tender Notice

निविदा नं. D /ISI /CIVIL WORK /2017 -2018 / 331

मोहरबंद लिफाफे में भरे हुए विवरण(quotation) आमंत्रित किए जाते हैं . विवरण(quotation) तारीख 08/02/2018 या उससे पहले इस कार्यालय को 3.00 बजे तक मिलने चाहिये . विवरण(quotation) उसी दिन आपके समक्ष या आपके अनुपस्थिति में 3.30 बजे खोले जायेंगे .

Name of work - Painting and window renovation works in A-10 ISI Campus Delhi Centre, New Delhi-110016

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
1	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	sqm	427.04		
2	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade :				
	Old work (one or more coats)	sqm	427.04		
3	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :				
	One or more coats on old work	sqm	168		
4	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.				
	for item no. 2 of 40%	sqm	170.81		
	Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete.				
5	Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides	sqm	8.6817		
	toilet T-1				
	15.0 DISMANTLING AND DEMOLISHING				
6	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
	For thickness of tiles above 25 mm and up to 40 mm	sqm	4.368		
7	Dismantling of flushing cistern of all types (C.I./PVC/Vitrious China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead.	each	3		
8	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931				
	15mm nominal bore	each	5		


Sr No.	Description of item of work	Unit	Qty	Rate	Amount
9	washbasin mixture single leaver	each	1		
10	Providing and fixing uplasticised PVC connection pipe with brass unions :				
	45 cm length				
	15 mm nominal bore	each	5		
11	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.				
	Flexible pipe				
	32 mm dia	each	1		
12	cp waste 1.25" inch	each	1		
13	fastners set-10 mm	each	4		
14	GI Bracket-25 mm x 25 mm	each	2		
15	floor trap	each	1		
16	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :				
	W.C. pan with ISI marked white solid plastic seat and lid	each	1		
	TOI-1				
	providing and fixing pipes/fitting astral make				
17	providing and fixing upvc pipe-3"	meter	1.4		
18	p/f floor trap-3" x 4"-upvc	each	1		
19	ss jali floor-4"--1 hole	each	1		
20	ss jali floor-4"--2 plain	each	2		
21	ss towel ring-8"	each	1		
22	p/f cp braa 2 in 1 bib cock	each	1		
23	p/f fixing cp flexible tube 1 mtr health fouch	each	1		
24	p/f cp paper holder	each	1		
25	p/f cp braa wall mixture	each	1		
26	p/f cp bra ss consealed -1/2"	each	2		
27	p/f cpvc MT-1/2" X3/4"	each	6		
28	p/f cpvc-ELBOW plain-3/4 "	each	2		
29	p/f cpvc-Tee plain-3/4 "	each	1		
30	p/f cpvc-pipe-1.5 mtr-3/4"	meter	1.5		
31	p/f cpvc-ELBOW brass-1/2"x 3/4 "	each	1		
32	over head shower-4" with arm	each	1		
33	Providing and fixing C.P. brass long body bib cock of approved quality conforming to IS standards and weighing not less than 690 gms.				
	15 mm nominal bore	each	1		
34	Dismantling old plaster or skirting/wall tile raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	sqm	1.161		
35	p/f GI Elbow-1/2"	each	2		

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
36	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick bed of cement mortar 1:4 (1 Cement : 4 Coarse sand), jointing with grey cement slurry @ 3.3kg/sqm including pointing the joints with white cement and matching pigments etc., complete.	sqm	4.368		
37	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	1.161		
38	12 mm cement plaster of neat cement punning mix :				
	1:4 (1 cement: 4 coarse sand)	sqm	0.9		
39	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.				
	Twin rubber stopper	each	4		
40	Repair to plaster of thickness 12mm to 20 mm in patches of area 2.5 sqm and under, including cutting the patch in proper shape, raking out joints and preparing plastering the wall surface with white cement based polymer modified self curing mortar, including disposal of rubbish, all complete as per the direction of Engineer-In- Charge.	sqm	1.8		
41	Providing and fixing ISI marked oxidised M.S. sliding door bolts with nuts and screws etc. complete :				
	300x16 mm	each	1		
42	Providing and fixing to existing door frames.				
	30 mm thick Glass Fibre Reinforced Plastic (FRP) panelled door shutter of required colour and approved brand and manufacture, made with fire - retardant grade unsaturated polyester resin, moulded to 3 mm thick FRP laminate for forming hollow rails and styles, with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings, cast monolithically with 5 mm thick FRP laminate for panels conforming to IS: 14856, including fixing to frames.	sqm	4.95		

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
43	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	125 mm	each	6		
44	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
	300x10 mm	each	3		
45	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete :				
	300x16 mm	each	3		
46	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required.				
	In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works	kg	5		
47	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :	each	18.708		
	Of area 3 sq. metres and below				
48	Floor polishing on masonry or concrete floors with wax polish of approved brand and manufacture.	sqm	101.31		
	Total(inclusive taxes)				
	extra taxes if any				
	Total(inclusive taxes)				
	Rebate/discount if any				
	Grand Total (inclusive taxes)				



अभियंता सिविल 'ए'


ओएसडी 1/2/2018

सूचना

1. प्रस्ताव देने के पहले विवरणकर्ता(quotationer) का जगह को देखना अनिवार्य है .
2. कार्य विवरण(specification) सहित व सिविल अभियंता के शमकश होना चाहिये .
3. कार्य आदेश मिलने के बाद 15 दिन के भीतर कार्य समाप्त होना चाहिए.
4. विवरणकर्ता(quotationer) विवरण फार्म(quotation) के साथ "पैन नम्बर " "(जीएसटी)-" नं. लगाना अनिवार्य है .
5. The quantity will be increased or decreased as per the actual site condition.
6. विवरण फार्म(quotation) सिग्नेचर किये बगैर और स्टाम्प लगाये बगैर मिला तो सीधे सीधे निरस्त किया जाएगा .
7. कोटेशन में दिए गए आपके कुल राशि पर टैक्सेज एप्लीकेबल रहेंगे.

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
--------	-----------------------------	------	-----	------	--------

8. माल ढुलाई का अतिरिक्त किराया भाड़ा या कुरियर भाड़ा नहीं दिया जायेगा.

9. सिक््योरिटी डिपोजिट ५% सुरक्षित जमा राशि आपके कुल राशि पर ६ महीने के लिए वैध रहेगी.

10. एडवांस राशि काम के पहले या बाद में एप्लीकेबल नहीं रहेंगे .

11. काम करते समय किसी भी प्रकार का हादसे के लिए ISI Delhi Centre जिमेदार नहीं रहेगी.

12. The ISI Delhi Centre reserve the right the whole tender process may be treated as a cancelled/terminated at any stage without assisgning any reason.

13. (जीएसटी- नं.) GST - No. is a mandatary from of 1ST JULLY 2017. Please enclosed GST Registration document.

14. For any clarification OSD may be contacted

15. The Quotationer Should be in PWD/ CPWD Registered. The Registration Document enclosing is must.

16. some items may or may not be operated at the time situational cndition.

प्रति :-

1. सूचना पलट

2. वेब स्थल आई एस आई दिल्ली केन्द्र