


भारतीय सांख्यिकी संस्थान
दिल्ली केंद्र

ग्राम स्टैटिस्टिक्स , नई दिल्ली
फ़ोन : .41493984
फैक्स : 41493981
ईमेल : kalam@isid.ac.in



7, एस जे एस, सनसनवाल मार्ग,
कुतुब हॉटल के पास
कटवरिया सराय नई दिल्ली

निविदा आमंत्रित सूचना
Tender Notice

निविदा नं. D /ISI /CIVIL WORK /2017 -2018 / 338

मोहरबंद लिफाफे में भरे हुए विवरण(quotation) आमंत्रित किए जाते हैं . विवरण(quotation) तारीख 14/03/2018 या उससे पहले इस कार्यालय को 3.00 बजे तक मिलने चाहिये . विवरण(quotation) उसी दिन आपके समक्ष या आपके अनुपस्थिति में 3.30 बजे खोले जायेंगे .

Name of work - Painting and other civil work in Electric Substation in ISI Campus Delhi Centre, New Delhi-110016.

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
1	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	sqm	839.24		
2	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade :				
	Old work (one or more coats)	sqm	839.24		
3	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the lastered wall surface to prepare the surface even and smooth complete.				
	same as item 1-40% paid only(AS PER TOTAL)	sqm	335.7		
4	Painting on G.S. sheet with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :				
	One or more coats on old work	sqm	123.35		
	15.0 DEMANTLING AND DEMOLISHING				
5	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.				
	In cement mortar	cum	1.152		
6	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying : a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours. The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.	sqm	9.25		

Sr No.	Description of item of work	Unit	Qty	Rate	Amount
7	Grading roof for water proofing treatment with				
	Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	cum	1.152		
8	12 mm cement plaster finished with a floating coat of neat cement of mix :				
	1:3 (1 cement: 3 fine sand)	sqm	9.25		
9	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.				
	Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix)	cum	0.144		
10	MALABA REMOVING	l/s	1		
11	Providing gola 75x75 mm in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 stone aggregate 10 mm and down gauge), including finishing with cement mortar 1:3 (1 cement : 3 fine sand) as per standard design :				
	In 75x75 mm deep chase	meter	10		
12	Raking out joints in lime or cement mortar and preparing the surface for repointing or replastering, including disposal of rubbish to the dumping ground within 50 metres lead.	sqm	9.86		
13	Flush pointing with cement mortar 1:3 (1 cement : 3 fine sand) mixed with 2% of integral water proofing compound by weight of cement for flat tile bricks on top of mud phaska :				
	With modular brick tiles	sqm	9.86		
14	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	sqm	8.876		
15	12 mm cement plaster of mix :				
	1:4 (1 cement: 4 fine sand)	sqm	8.876		
16	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, IS : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank.				
	Circular tank	ltr	1000		
17	Dismantling G.I. pipes (external work) including excavation and refilling trenches after taking out the pipes, manually/ by mechanical means including stacking of pipes within 50 metres lead as per direction of Engineer-in-charge :				
	15 mm to 40 mm nominal bore	meter	12		
18	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required.				
	In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works				